

## Datasheet-12micron Hand Stretch Wrap

Item: 12mic\*300mm\*450m

Color: Clear

LLDPE Stretch Film,excellent puncture resistance, good self-adhension, widely used in pallet packing of bulk goods during transportation or warehouse storage

ITEM	UNIT	REFERENCE VALUE	TEST METHOD
THICKNESS	48gauge	0.012mm±0.002mm	GB7125-1999
WIDTH	300mm	300mm±2mm	GB7125-1999
LENGTH	450	450meters±5m	GB7125-1999
CORE LENGTH	300	300mm±2mm	GB7125-1999
CORE DIAMETER	3"	76mm±2mm	GB7125-1999
WEIGHT	KG	NW:1.48KG±0.05kg	GB7125-1999
		GW: 1.7KG±0.05kg	
TENSILE STRENGTH	Mpa	MD≥38	ASTMD-GB13022
		TD≥32	
ELONGATION BREAK	%	MD≥300	ASTMD-GB13022
		TD≥330	
ADHESIVE	N/10CM	>0.8	HT
FOG DENSITY	%	<2	ASTMD-GB2410
TEMPERATURE RESISTANCE	℃	≤90	
PE	100%	100%	

The above hand stretch wrap is made of 100% Virgin Raw Material

### FEATURES

1.Substrate Material: LLDPE+MLDPE 2.Density: 0.00916

Test Date: 2022-7-20

Test Machines:thickness Gauge,tape measure,callipers,Pulling force testing machine

Storage: room temperature,Please avoid to heavily throw and used in the abnormal environment.