

Product Technical Datasheet								
产品名称 Product Name		9层真空袋 9layer Vacuum Pouch						
膜厚 Gauge		40 μ m -200 μ m						
测试项目 Test project		单位 Unit	检测方法 Test Method	指标 SPEC				
宽度偏差 Width deviation		mm	ISO4592	±3mm (最宽800mm) (max wide 800mm)				
长度偏差 Length deviation		mm	ISO4592	±3mm				
厚度 Thickness		平均厚度Ave	ISO4593	±3 %				
		极限厚度Limi		±8 %				
拉伸强度 Tensile Strength			ASTMD882	65um	70um	80um	100um	
		MD		Mpa	≥23	≥25	≥25	≥25
		TD			≥23	≥25	≥25	≥25
断裂延长率 Elongation at Break		MD		≥360	≥380	≥400	≥400	
		TD		≥360	≥380	≥400	≥400	
热封强度 Heat Seal Strength		MD	N/15mm	ASTMF2029	≥15	≥18	≥22	≥26
剥离力 Intermediate Peeling			N	DIN 53357	≥7	≥7	≥7	≥7
雾度 Haze			%	ASTMD1003	≤15	≤15	≤18	≤22
透光率 Transparency			%		≥90	≥90	≥90	≥85
摩擦系数 C. O. F.	静 US		in/in	ASTMD1894	≤0.4	≤0.4	≤0.4	≤0.4
	动 UD		in/in		≤0.4	≤0.4	≤0.4	≤0.4
透氧 OTR (at 23°C, Dry , 1atm)			cm <sup>3</sup> /m <sup>2</sup> *24h	ASTMD3985	≤110	≤100	≤80	≤60
备注 NOTE		符合FDA标准 FDA Approved						